# Aluminium



# 4800

# Series Strikes

4800 Series Strikes add aesthetics and finish to strike cutouts in metal or wood jambs.

## 4800

With vertical adjustment to accommodate door/jamb misalignment and a shim system for horizontal positioning to match various jamb bumper designs, the 4800 Series Strikes can be fit to nearly any sliding door using a mortised MS1847 Deadlock/Deadlatch.

#### **Materials**

Steel, heat treated. Shims are ABS plastic. Available in choice of Zinc (603) finish, US32D (630) Satin Stainless.

#### 4801



# MS4804

This reinforcing strike provides strength equal to the strength of the stainless steel bolt of the MS1847 Deadlock/Deadlatch: tested to 1000 lbs [453.59 kg] of force. This strength by far exceeds the standards of the Architectural Aluminum Manufacturers Association as well as the strictest current municipal security ordinance.

#### Faceplate

Measures 1/16"  $\times$  3/4"  $\times$  3-3/8" [1.6 mm  $\times$  19.1 mm  $\times$  85.7 mm]. Steel, plated for corrosion resistance. MS4804-10 available in US32D (630) Satin Stainless.

#### **Reinforcing Plate**

Measures 1/16"  $\times$  1/2"  $\times$  3-3/8" [1.6 mm  $\times$  12.7 mm  $\times$  85.7 mm]. Steel, plated for corrosion resistance. Tapped for furnished #10-32 flathead screws.

# 4804

# **Features**

#### Standard Package

All strikes are individually packaged with screws and shim if required.

**4801 Strikes** are furnished with sheet metal screws for metal jamb installation.

**4802 Strikes** are furnished with machine screws and tee nuts which are installed on the back side of the jamb to provide the strongest possible anchorage in wood.


#### **Shipping Weight**

1/2 lb [0.23 kg]






# Dimensions 4800 Series




APPLICATION	PART NO.	SHIMS	DIMENSION 'A'
	4801	NONE	0
Metal jambs	4801-01	1	3/32" (2.4mm)
(furnished with two #8 x 1 sheet metal screws	4801-02	2	3/16" (4.8mm)
sneet metal screws	4801-03	3	9/32" (7.1mm)
	4802	NONE	0
Wood jambs (furnished with	4802-01	1	3/32" (2.4mm)
two #8-32 x 7/8" machine screws and two tee nuts)	4802-02	2	3/16" (4.8mm)
	4802-03	3	9/32" (7.1mm)

# Jamb Preparation **4800** Series


	HOLE SIZE		
Metal jamb application 4801 series	1/8" 3.2mm	(No. 31 DRILL)	
Wood jamb application 4802 series	7/32" 5.6mm	(No. 3 DRILL)	



### MS4804



### MS4804



# How to Order & Compatible Products

4800, MS4804 Strikes: Specify quantity and the following information. Order related products separately.

MODEL	TYPE OF JAMB	DIMENSION 'A'	FINISH
480	1	-02	-630
	1 Metal	<b>01</b> 3/32" (2.4mm)	603 Zinc Plated Steel
	2 Wood	<b>02</b> 3/16" (4.8mm)	<b>630</b> Satin Stainless
		<b>03</b> 9/32" (7.1mm)	

#### Compatible

DEADLOCKS	
MS1847 Deadlock/Deadlatch	