#### AMANO WIEGAND READER

## AMANO WJB

# Amano WJB

**Wiegand Single Gang Reader** 

#### **KEY FEATURES**

- Communications distance of up to 500 feet (150 m).
- Designed to connect directly to a standard switch box for easy installation.
- Multiple Wiegand output formats (26-bit and 44-bit).
- Read capability from various tag types: Slim Tags, Omega Tags, Amano Trinary Tags (1074 and 2074) and HID Tags (H10301, H10302 and H10304).
- A single tri-colored Red, Green or Amber Status LED.
- A 4 kHz piezo-electric Buzzer.
- An external Wiegand communications bus interface.
- Fully potted for vandal resistant outdoor use
- Dual input voltage types supported (5 V DC and 12 V DC).



Amano WJB Single Gang Reader

#### **PHYSICAL SPECIFICATIONS**

Dimensions (H x W x D)	4.7" x 2.8" x 0.74" (120mm x 72mm x 19mm)
Weight	5.1 oz (144.8g)
Housing Material	ABS plastic
Color	Black

#### **ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature	-4°F to +140°F (-20°C to +60°C)
Storage Temperature	-40°F to +176°F (-40°C to +80°C)
Humidity Range	0 to 95% relative humidity at +104°F (+40°C) non-condensing.
CE Approval	EN301 489-3, EN301 489-1 and EN300 330-1.
FCC Approval	Pending.
Dust & Splash Resistance	Designed to work in an indoor or protected outdoor environments sim- ilar to IP54.



## **ELECTRICAL SPECIFICATIONS**

#### POWER

Input Voltage Rating	5 V DC to 16 V D	5 V DC to 16 V DC, polarity sensitive.	
Power Requirements	Current (mA)	Power (W)	
Supply Voltage 5 V DC all indicators on	50	0.25	
Supply Voltage 12 V DC all indicators on	50	0.60	
Permissible Input Supply Ripple Voltage (Max)	1 V pp at 50 Hz	1 V pp at 50 Hz	
Power Input Protection	Reverse polarity p	Reverse polarity protection is provided on the Reader.	

#### WIEGAND BUS

Electrical Interface	'0' and '1' data streams.
Tag Information Data Format	44-bit Wiegand or 26-bit Wiegand.

#### **INPUTS**

Quantity	4
Туре	Dry Contact.
Function	Operation of the Buzzer, LED and Scanner Inhibit.

#### **USER INTERFACES**

#### BUZZER

Volume & Tone

4 kHz piezo-electric, single volume, single tone.

#### **STATUS INDICATOR**

Status LED

Tri-colored Red, Green or Amber (Default) (externally visible).

## AMANO.

**ORDERING INFORMATION** 

WJB900-1-0-AC Amano Single Gang Reader

Amano reserves the right to change specifications without prior notice.