

# Amano WPK

## Wiegand Plastic Keypad Reader

### KEY FEATURES

- ◆ Communications distance of up to 500 feet (150 m).
- ◆ Suitable for OEM developments.
- ◆ Multiple Wiegand output formats (26-bit and 44-bit).
- ◆ Read capability from various tag types: Slim Tags, Omega Tags, Amano Trinary Tags (1074 and 2074) and HID Tags (H10301, H10302 and H10304).
- ◆ A single tri-colored Red, Green or Amber Status LED.
- ◆ A 4 kHz piezo-electric Buzzer.
- ◆ 12-Button alphanumeric keypad
- ◆ An external Wiegand communications bus interface.
- ◆ Dual input voltage types supported (5 V DC and 12 V DC).
- ◆ Programmable facility code for use with PIN-code entry.



**Amano WPK Plastic Keypad Reader**

### PHYSICAL SPECIFICATIONS

<b>Dimensions (H x W x D)</b>	4.44" x 3.19" x 1.26" (113mm x 81mm x 32mm)
<b>Weight</b>	6.5 oz (185g)
<b>Housing Material</b>	ABS Plastic.
<b>Color</b>	Dark Gray

### ENVIRONMENTAL SPECIFICATIONS

<b>Operating Temperature</b>	-13°F to +140°F (-25°C to +60°C)
<b>Storage Temperature</b>	-40°F to +176°F (-40°C to +80°C)
<b>Humidity Range</b>	0 to 95% relative humidity at +104°F (+40°C) non-condensing.
<b>CE Approval</b>	EN301 489-3, EN301 489-1 and EN300 330-1.
<b>FCC Approval</b>	Pending.
<b>Dust &amp; Splash Resistance</b>	Designed to work in indoor or outdoor environments similar to IP53.



## ELECTRICAL SPECIFICATIONS

### POWER

<b>Input Voltage Rating</b>	5 V DC to 16 V DC, polarity sensitive.	
<i>Power Requirements</i>	<i>Current (mA)</i>	<i>Power (W)</i>
<b>Supply Voltage 5 V DC all indicators on</b>	50	0.25
<b>Supply Voltage 12 V DC all indicators on</b>	50	0.60
<b>Permissible Input Supply Ripple Voltage (Max)</b>	1 V pp at 50 Hz	
<b>Power Input Protection</b>	Reverse polarity protection is provided on the Reader.	

### PIN-CODES

<b>Type</b>	5 Digit codes in the range 00000 to 65535. 4 Digit codes in the range 0000# to 9999#.
-------------	--

### WIEGAND BUS

<b>Electrical Interface</b>	'0' and '1' data streams.
<b>Tag Information Data Format</b>	44-bit Wiegand or 26-bit Wiegand.
<b>Key Information Data Format</b>	26-bit Wiegand only.

### INPUTS

<b>Quantity</b>	4
<b>Type</b>	Dry Contact.
<b>Function</b>	Operation of the Buzzer, LED and Scanner Inhibit.

## USER INTERFACES

### BUZZER

<b>Volume &amp; Tone</b>	4 kHz piezo-electric, single volume, single tone.
--------------------------	---

### KEYPAD

<b>Keys</b>	12 Alphanumeric keys.
-------------	-----------------------

### STATUS INDICATOR

<b>Status LED</b>	Tri-colored Red, Green or Amber (Default) (externally visible).
-------------------	---

## ORDERING INFORMATION

WPK900-1-0-AC Amano ABS Plastic Keypad Proximity Card Reader (Multi-mode)

*Amano reserves the right to change specifications without prior notice.*