

# The Falcon 24 and 25 Series

## **The perfectly simple, tougher than nails, costs less than you think, fits anywhere exit device.**

Offices, banks, assisted living facilities, retail stores and other commercial buildings have constant traffic, so door hardware must be able to take continual use and abuse. The Falcon 24 and 25 Series exit devices fill the bill with some of the toughest, most reliable performance in the business. A host of features makes this a smart solution, like a choice of an A or B label fire rating, electrified and panic options, and a full complement of trims. Sleek, streamlined styling and a choice of wide (25 Series) and narrow stile (24 Series) device applications means a smart solution for your building design, as well as its use. And since they're backed by one of the best names in the business, you can be sure you're getting the utmost value, reliability and durability.

## Features


Streamlined design includes flush-end cap for clean lines and a more attractive installation.

Clean design with no exposed screws or rivets on the back of the device.

Patent-pending deadlocking technology ensures reliable security.

One trim input design for maximum versatility.

Extruded aluminum construction delivers greater strength and impact resistance.



# Falcon exit devices

## Architectural pushpads

## Commercial pushpads



### 24/25 Series

### 19 Series


### 1490/1590

### 1690/1790

|                  |   |  |  |  |  |
|------------------|---|--|--|--|--|
| Selling features | <ul style="list-style-type: none"> <li>• Maximum flexibility in a variety of applications</li> <li>• Wide range of features and options</li> <li>• Patent pending deadlocking technology</li> </ul> | <ul style="list-style-type: none"> <li>• Lowest cost most dependable light-duty exit</li> <li>• Large trim selection</li> <li>• Standard deadlocking</li> </ul>  | <ul style="list-style-type: none"> <li>• Steel operating mechanisms</li> <li>• Aluminum push bar and end caps</li> <li>• Durable design</li> <li>• Surface vertical and rim options available</li> </ul> | <ul style="list-style-type: none"> <li>• Patented pending latchbolt for hurricane ratings</li> <li>• #1 selling exit device for aluminum doors</li> <li>• Full compliment of electrical options</li> <li>• Durable design</li> </ul> |  |
|                  | Applications  | <ul style="list-style-type: none"> <li>• Frequent traffic</li> <li>• Offices, churches, hospitality, retail, education, healthcare</li> <li>• Interior, exterior, new construction, retro-fit</li> </ul> | <ul style="list-style-type: none"> <li>• Moderate traffic</li> <li>• Commercial, multi-family, office, retail</li> <li>• Interior, exterior, retro-fit</li> </ul>  | <ul style="list-style-type: none"> <li>• Moderate traffic</li> <li>• Commercial, multi-family, office, retail</li> <li>• Interior, exterior, retro-fit</li> </ul>  | <ul style="list-style-type: none"> <li>• Moderate traffic</li> <li>• Commercial, multi-family, office, retail</li> <li>• Interior, exterior, retro-fit</li> </ul>  |
|                  | Device options  | <ul style="list-style-type: none"> <li>• Rim, SV, CV, M</li> <li>• 6 functions /9 finishes</li> <li>• 4 lever designs</li> <li>• 10-year warranty</li> </ul>   | <ul style="list-style-type: none"> <li>• Rim, SV</li> <li>• 7 functions /4 lever designs</li> <li>• 3 finishes</li> <li>• 10-year warranty</li> </ul>  | <ul style="list-style-type: none"> <li>• CV=1490/Rim=1590</li> <li>• 4 functions/10 finishes</li> <li>• 3 length options</li> <li>• 10-year warranty</li> </ul>  | <ul style="list-style-type: none"> <li>• CV = 1690/Rim = 1790</li> <li>• 4 functions/7 finishes</li> <li>• 4 length options</li> <li>• 10-year warranty</li> </ul> |

## Crossbars

## Recessed/ concealed devices



### XX

### 1990

### 2090

### 2390

|   |  |   |  |
|---|--|---|--|
| <ul style="list-style-type: none"> <li>• Classic traditional design</li> <li>• Dependable and attractive</li> <li>• Economic crossbar option</li> <li>• Panic and fire rated options</li> </ul> | <ul style="list-style-type: none"> <li>• Classic industry look</li> <li>• Balanced appearance, dependable performance and economical pricing</li> <li>• Hardened steel latches</li> <li>• Adjustable strike to ensure safety, security and smooth operation</li> </ul> | <ul style="list-style-type: none"> <li>• Classic looks in a rim device</li> <li>• Designed for high use and abuse</li> <li>• 1/2" inch steel latchbolt</li> <li>• Surface mounted strikes for full frame or blade type stops</li> </ul> | <ul style="list-style-type: none"> <li>• Reduced projection recessed device</li> <li>• Tough, reliable performance</li> <li>• Easy rod adjustment simplifies installation</li> <li>• Smooth, reliable operation</li> </ul> |
| <ul style="list-style-type: none"> <li>• Light/moderate traffic</li> <li>• Commercial, multi-family, office, retail</li> <li>• Interior, exterior, retro-fit</li> </ul>                         | <ul style="list-style-type: none"> <li>• Light traffic</li> <li>• Commercial, multi-family, office, retail</li> <li>• Interior, exterior, retro-fit</li> </ul>   | <ul style="list-style-type: none"> <li>• Light traffic</li> <li>• Commercial, multi-family, office, retail</li> <li>• Interior, exterior, retro-fit</li> </ul>  | <ul style="list-style-type: none"> <li>• Moderate/ frequent traffic</li> <li>• Healthcare, assisted living, education</li> <li>• Interior, new construction</li> </ul>   |
| <ul style="list-style-type: none"> <li>• Rim, SV, CV, M</li> <li>• 13 functions/8 finishes</li> <li>• 5 lever options</li> <li>• 10-year warranty</li> </ul>                                    | <ul style="list-style-type: none"> <li>• CV</li> <li>• 4 functions/10 finishes</li> <li>• 2 length options</li> <li>• 10-year warranty</li> </ul>  | <ul style="list-style-type: none"> <li>• Rim</li> <li>• 4 functions/10 finishes</li> <li>• 2 length options</li> <li>• 10-year warranty</li> </ul>  | <ul style="list-style-type: none"> <li>• CV</li> <li>• 3 functions/4 finishes</li> <li>• 2 length options</li> <li>• 10-year warranty</li> </ul>   |

# F-25-C Series

## Concealed vertical rod device

### 🔥 Fire exit hardware

The Falcon F-25-C Series device lets you combine the safety of a fire-rated device with the clean aesthetics that come with a concealed vertical rod installation. In-field adjustment is simple thanks to our patented center slide mechanism. Two-point latching ensures optimal security at the door.



### Specifications

|                        |   |
|------------------------|---|
| Hand:                  | Field reversible  |
| UL:                    | "A" label (3 hr.); 4'0" x 10'0" single doors; 8'0" x 10'0" pair of doors (F-25-M x F-25-V or F-25-C).   |
| Finishes:              | US3 (605); US4 (606); US10 (612); US11 (643e); US15 (619); US19 (622); US26 (625); US26D (626); US32 (629); US32D (630); US28 (628), 313AN (710) (see page 17 for finishes).          |
| Strikes:               | 4188 mortised top, 2130 bottom standard   |
| Latchbolt:             | Stainless steel, 3/4" throw.  |
| Deadlocking latchbolt: | Standard  |
| Stock sizes            | See chart   |
| Doors:                 | 1 3/4" thick, wood or metal. Specify thickness if other than 1 3/4".  |
| Projection:            | 2 3/4" maximum  |
| Stile:                 | 4" minimum  |
| Mounting height        | 40 1/4" from CL to finished floor   |
| Electric functions:    | Can be interfaced with building security systems. Motorized electric latch retraction (fail secure only), FSA/FSE trim, security monitoring, delayed egress and exit alarm available. |
| Fasteners:             | All mounting screws are concealed. All machine screws (AMS) standard.   |
| Sex bolts:             | Required when used with wood, composite or non-reinforced hollow metal doors. For EO device specify 6 - 425 (#10-24) SNB. For devices with trim, specify 2 - 425 (#10-24) SNB.        |
| ANSI:                  | Certified ANSI A156.3-2001 grade 1 standards.   |
| 25-C-LBR:              | Less bottom rod, auxiliary fire pin required per pair   |
| Vertical rods:         | Furnished to length based on 40 1/4" horizontal CL to finished floor and a 7'0" door. Variations from these standards must be specified when ordering.                                |
| Shim kits:             | Consult factory   |

| Device | Door size | Door strike | Min stile (in)             | Min door opening width |
|--------|-----------|-------------|----------------------------|------------------------|
| 25-C   | 3'        | All         | 4" (6 1/2" for wood doors) | 2' 7 1/8"              |
| 25-C   | 4'        | All         | 4" (6 1/2" for wood doors) | 3' 1 1/8"              |

# 25 Series

## Strikes and accessories

### Strikes

#### For rim devices



**264**  
2 7/8" x 1 1/4" x 9/16"  
(H x W x D)  
Panic device only.



**299**  
7 7/8" x 1 1/4" x 13/16"  
(H x W x D)  
Panic device only.



**299F**  
2 7/8" x 1 1/4" x 13/16"  
(H x W x D)



**499F**  
3 5/8" x 1 1/2" x 16/16"  
(H x W x D)



**1439 Blade stop**  
1 3/4" x 1 7/8" x 1/2"  
(H x W x D)  
Panic device only.



**1606**  
2 7/8" x 1 3/8" x 3/8"  
(H x W x D)  
Panic device only.



**1609**  
3 1/4" x 1 1/16" x 3/8"  
(H x W x D)  
Requires coordinator.  
Panic device only.

#### For surface and concealed vertical rod devices



**2130**  
(F)25-V and (F)25-C  
standard bottom strike for  
grouting into concrete or  
masonry floors.



**3788**  
Furnished top  
of (F)25-V.



**4155**  
Optional strike.  
Panic device only.




**4188**  
Top strike for  
(F)25-C.

#### For mortise lock devices



**1279**  
Closed strike used on  
single doors and on fire  
exit hardware doors with  
coordinator.




**F1280**  
Open back strike used on pairs of  
1 3/4" doors without astragal or  
coordinator. Can be used on stock  
hollow metal doors. F1280 "B" label  
(1 1/2 hr.) stainless steel strike  
available.



**1281**  
Open back strike for 1 3/4" doors.  
8" x 1 1/4" face allow use in  
mortise lock cutout of stock  
hollow metal door.

### Accessories



**4215**  
Angle bracket for flush transom applications.  
Does not require elimination of latch retention  
feature. Accepts 3788 strike for 25-V device.

#### Surface vertical extension rods

Extension rods are available in 12", 24" and 36" lengths in all finishes. Both ends tapped and all-thread included as connector.




#### Concealed extension rods

Extension rods are available in 12", 24" and 36". Both ends have pressed-in, threaded inserts.



#### Filler Plates



#### 3721/ 3722/ 3723

Steel filler plates


- 3721 Cylindrical lock front filler
- 3722 Strike filler - set no. SC for 161 cutout
- 3723 Mortise lock front filler
- 3722 Strike filler - set no. SM for 86 cutout

# 25 Series

## Trim designs

Functionality built into the trim, facilitating easy door preps, easy field retrofit and easy ordering.

### Lever trims (510L)



510L  
510L-NL      510L-DT  
510L-BE

### Lever designs



**Avalon (AVA)**  
Projection 3 1/4"



**Quantum (QUA)**  
Projection 3 1/4"



**Dane (DAN)**  
Projection 3"



**Broadway (BRW)**  
Projection 3 1/5"



**Boardwalk (BRK)**  
Projection 3 1/5"



**Danish (DSH)**  
Projection 2 9/16"



**Latitude (LAT)**  
Projection 3 1/16"



**Longitude (LON)**  
Projection 3 1/16"



**Sutro (SUT)**  
Projection 3 1/4"

All levers return to within 1/2" of door.  
Escutcheon: 9 3/4" (H) x 2 3/4" (W) (specify handing) brass finish.  
Protected by easily replaceable shear pin.  
Lever is reversible, supplied RHR if not specified. For keyed functions, see page 14 for cylinder requirements.

### Vandal - resistant lever trims (511L)



Provides resistance to rotation, making damage of trim due to attack from the outside less likely. Designed to operate normally after vandalism attempts without the need for maintenance personnel intervention.

- Heavy duty, vandal-resistant, ANSI A156.3 grade 1 security trim
- Lever deflects up to 22 ft-lb for a minimum of 10,000 vandal-resistant cycles
- Vandal resistance is present in both lever rotation directions
- After lever is fully deflected, lever stops rotating and a shear pin breaks at 70 ft-lb to prevent damage to unit
- Available on 25 rim, vertical, mortise, and concealed devices
- Retrofits all existing 25 trim without additional door prep
- Works with all electric lock and unlock functions
- Available in all finishes and lever designs including Avalon, Boardwalk, Broadway, Dane, Danish, Latitude, Longitude, Sutro, and Quantum

### Pull trims (512)



512TP      512NL      512DT      512TP-BE      717DT

Escutcheon: 16" x 2 3/4"  
Grip: 6 1/4" C-C  
Projection: 2 11/16"  
Brass  
For keyed functions, see page 14 for cylinder requirements.

### Delta (717)

### Knob trims (513K)



513K-DT      513K  
513K-BE      513K-NL

Round ball knob  
Escutcheon: 9 3/4" x 2 3/4"  
Projection: 4"  
Brass  
For keyed functions, see page 14 for cylinder requirements.

### Cylinder only (NL-OP)

Key retracts latch bolt.  
Cylinder sold separately (see page 14).













# 25 Series

## Trim chart & finish chart

### Function

|                              | Lock/ unlock | NL      | DT      | BE       | FSA/ FSE             |
|------------------------------|--------------|---------|---------|----------|----------------------|
| Lever (510)                  | 510L         | 510L-NL | 510-DT  | 510L-BE  | 510L-FSA<br>510L-FSE |
| Vandal-resistant lever (511) | 511L         | —       | —       | —        | 511L-FSA<br>511L-FSE |
| Pull trims (512)             | 512TP        | 512-NL  | 512DT   | 512TP-BE | 512L-FSA<br>512L-FSE |
| Knob (513)                   | 513K         | 513K-NL | 513K-DT | 513K-BE  | 513L-FSA<br>513L-FSE |
| Delta (717)                  | —            | —       | 717DT   | —        | —                    |

## 25 Series finishes

























|   | Color                   | US number | BHMA number |
|---|-------------------------|-----------|-------------|
|   | Brass, bright           | US3       | 605         |
|  | Brass, satin            | US4       | 606         |
|  | Bronze, satin           | US10      | 612         |
|  | Bronze, aged            | US11      | 643e*       |
|  | Nickel, satin           | US15      | 619*        |
|  | Black, matte            | US19      | 622*        |
|  | Chromium, bright        | US26      | 625         |
|  | Chromium, satin         | US26D     | 626         |
|  | Anodized aluminum       | US28      | 628         |
|  | Stainless Steel, bright | US32      | 629         |
|  | Stainless Steel, satin  | US32D     | 630         |
|  | Anodized duranodic      | 313AN     | 710         |

\*Available on select devices and trims

# 25 Series

## Types and functions


This page shows all 25 Series device and trim functions.

|   | Rim device<br>ANSI type 1  | Vertical rod<br>device<br>ANSI type 2  | Mortise lock<br>device<br>ANSI type 3  | Concealed vertical<br>rod device<br>ANSI type 8  |
|---|--|--|--|--|
| Functions (ANSI)  | (F)-25-R   | (F)-25-V   | (F)-25-M   | (F)-25-C   |
| <b>EO (01)</b><br>Exit only,<br>no trim.  | <br><b>25-R-EO</b>        | <br><b>25-V-EO</b>        | <br><b>25-M-EO</b>        | <br><b>25-C-EO</b>        |
| <b>DT (02)</b><br>Entrance by trim<br>when actuating bar<br>is locked down.   | <br><b>25-R-DT</b>        | <br><b>25-V-DT</b>        | <br><b>25-M-DT</b>        | <br><b>25-C-DT</b>        |
| <b>NL (03)</b><br>Entrance by trim<br>when latchbolt is<br>retracted by key.<br>Key removable<br>only when locked.  | <br><b>25-R-NL</b>      | <br><b>25-V-NL</b>      | <br><b>25-M-NL</b>      | <br><b>25-C-NL</b>      |
| <b>TP (05)</b><br>Entrance by<br>thumbpiece.<br>Key locks or<br>unlocks<br>thumbpiece.  | <br><b>25-R-TP</b>      | <br><b>25-V-TP</b>      | <br><b>25-M-TP</b>      | <br><b>25-C-TP</b>      |
| <b>L or K (08)</b><br>Entrance by knob<br>or lever. Key locks<br>or unlocks knob.   | <br><b>25-R-L/K</b>     | <br><b>25-V-L/K</b>     | <br><b>25-M-L/K</b>     | <br><b>25-C-L/K</b>     |
| <b>L(NL) or K(NL) (03)</b><br>Entrance by knob<br>or lever when latchbolt<br>is retracted by key.<br>Lever/knob is rigid.<br>Key removable only<br>when locked. | <br><b>25-R-L/K(NL)</b> | <br><b>25-V-L/K(NL)</b> | <br><b>25-M-L/K(NL)</b> | <br><b>25-C-L/K(NL)</b> |

# 25 Series

## Door application



### Label doors

Models F-25-R, F-25-M, F-25-C and F-25-V are labeled for use as  Fire exit hardware.

### Door thickness

All devices and components supplied for 1 3/4" doors standard. Specify door thickness if other than 1 3/4".

### Door application chart



Product information and specifications contained in this catalog are subject to change without notice. Please consult the factory.



# Motorized electric latch retraction

## Motorized electric latch retraction (MEL) for 24 and 25 Series devices

Motorized electric latch retraction (MEL) provides energy efficient electronic control of an exit device for an affordable around the door solution. The MEL option is Falcon's solution of choice for multifamily and commercial real estate facilities where cost competitive electromechanical latch retraction is desired. It is available on most Falcon 24 and 25 Series exit devices (not available for mortise 25-M or F-25-M).

These devices always provide mechanical egress. Motorized electric latch retraction can be used with credential readers to unlatch doors momentarily for authorized users, or it can be incorporated with systems to retract latches for extended periods of time to allow free entry. This is a convenient alternative to mechanical dogging. Doors with automatic operators also may use exit devices with electric latch retraction.

The MEL option is available on panic and fire rated devices. Because fire exit hardware must be self latching, an automatic fire alarm system must be incorporated to drop power to fire rated MEL devices in case of fire.

### Features and benefits

- MEL option available on 24 and 25 Series exit devices, except 25-M (mortise)
- Energy efficient motorized latch retraction enables longer wire runs and the use of a standard Schlage power supply with option board (see page 33)
- Modular design allows for a simplified installation of the available MEL Conversion kit to existing mechanical Falcon 24 or 25 exit devices
- On-board installation and troubleshooting diagnostics built into the motor assembly
- Self-calibrating motor assembly
- Pushbar is pulled in electronically when dogged
- Vandal resistant – detects and responds to events of attack and tampering

### MEL system requirements

The MEL has a low inrush current = 1.0 amps, so it can be used with standard Schlage power supplies. When powering multiple components, verify that the amperage requirement of all components combined does not exceed the power supply output rating.

- The MEL device is compatible with the following equipment: PS900 Series power supplies - PS902, 904, 906, 914; 900 Series Option Boards - 900-2RS, 900-4R and 900-4RL
- A power transfer (EPT, electrified hinge, or door loop) is required and sold separately

### Compatible options

- Security monitoring (DM, LM, RX)
- Fail Safe/Fail Secure electric trim (FSA/FSE)

### How to order:

- To order the MEL feature add "MEL" prefix to device designation (example: MEL-25-R-EO)<sup>1</sup>
- To order the MEL feature with Allegion Connect, add "MEL" prefix and "CON" suffix to device designation
- To order the MEL conversion kit, please specify finish with part number (US3, US4, US10, US26, US26D, US32D, SP28, SP313)<sup>2</sup>

1. Mechanical dogging is not an option with MEL.

2. MEL kits may not be used to convert an EL device. MEL conversion kits are only compatible with mechanical Falcon 24 and 25 series exit devices.




| Model no. | Description                                   | Part number | Part number with Allegion Connect (-CON) |
|-----------|---|-------------|--|
| 25-MELK-3 | 25 Motorized electric latch retraction kit 3' | 47266630    | 47266630                                 |
| 25-MELK-4 | 25 Motorized electric latch retraction kit 4' | 47266631    | 47266631                                 |
| 24-MELK-3 | 24 Motorized electric latch retraction kit 3' | 47266632    | 47266632                                 |
| 24-MELK-4 | 24 Motorized electric latch retraction kit 4' | 47266633    | 47266633                                 |

# Motorized electric latch retraction

## Application and wiring

### Popular application and wiring - motorized electric latch retraction (MEL)



Popular application shown above.  
See page 39 for other power supply details.

| Device   | Door size | Door strike | Minimum door opening width (Add 3.5" to standard) |
|----------|-----------|-------------|---|
| MEL-24-R | 3'        | 299         | 2' 11"  |
|          |           | 264         | 2' 10 <sup>7</sup> / <sub>8</sub> "               |
|          |           | 1439        | 2' 10 <sup>1</sup> / <sub>4</sub> "               |
|          |           | 1606        | 2' 10 <sup>5</sup> / <sub>8</sub> "               |
| MEL-24-R | 4'        | 299         | 3' 5"   |
|          |           | 264         | 3' 4 <sup>7</sup> / <sub>8</sub> "                |
|          |           | 1439        | 3' 4 <sup>1</sup> / <sub>4</sub> "                |
|          |           | 1606        | 3' 4 <sup>5</sup> / <sub>8</sub> "                |
| MEL-24-C | 3'        | All         | 2' 10 <sup>5</sup> / <sub>8</sub> "               |
| MEL-24-C | 4'        | All         | 3' 4 <sup>5</sup> / <sub>8</sub> "                |
| MEL-24-V | 3'        | All         | 2' 10 <sup>5</sup> / <sub>8</sub> "               |
| MEL-24-V | 4'        | All         | 3' 4 <sup>5</sup> / <sub>8</sub> "                |
| MEL-25-R | 3'        | 299         | 2' 11"  |
|          |           | 264         | 2' 10 <sup>7</sup> / <sub>8</sub> "               |
|          |           | 1439        | 2' 10 <sup>1</sup> / <sub>4</sub> "               |
|          |           | 1606        | 2' 10 <sup>5</sup> / <sub>8</sub> "               |
| MEL-25-R | 4'        | 299         | 3' 5"   |
|          |           | 264         | 3' 4 <sup>7</sup> / <sub>8</sub> "                |
|          |           | 1439        | 3' 4 <sup>1</sup> / <sub>4</sub> "                |
|          |           | 1606        | 3' 4 <sup>5</sup> / <sub>8</sub> "                |
| MEL-25-C | 3'        | All         | 2' 10 <sup>5</sup> / <sub>8</sub> "               |
| MEL-25-C | 4'        | All         | 3' 4 <sup>5</sup> / <sub>8</sub> "                |
| MEL-25-V | 3'        | All         | 2' 10 <sup>5</sup> / <sub>8</sub> "               |
| MEL-25-V | 4'        | All         | 3' 4 <sup>5</sup> / <sub>8</sub> "                |

### Power transfer - motorized electric latch retraction (MEL)

A power transfer (EPT, electrified hinge, door loop) provides a wiring path from the door to the frame. If an EPT (Electric Power Transfer) is utilized, the door and frame must be factory prepped.

#### EPT options

- EPT-2: Two 18AWG wires with a max rating of 24VDC, 5A or 120 VAC NEC class 3
- EPT-10: Ten 24AWG wires with a max rating of 24VDC, 1A

| EPT can be used for:   | EPT cannot be used for:                       |
|--|---|
| Door thickness - 1 <sup>3</sup> / <sub>4</sub> " minimum                                 | 1 <sup>1</sup> / <sub>2</sub> " offset pivots |
| 0-180 degree opening with up to 5" butt hinges <sup>1</sup>                              | Larger than 6" butt hinges                    |
| 0-130 degree opening with up to 5 <sup>1</sup> / <sub>2</sub> " butt hinges <sup>1</sup> | Pocket pivots                                 |
| 0-110 degree opening with up to 6" butt hinges <sup>1</sup>                              | Swing clear hinges                            |
| 0-180 degree opening with up to <sup>3</sup> / <sub>4</sub> " offset pivots <sup>1</sup> | Center hung doors (center pivot)              |
|  | Balanced door                                 |

1. Specifications only apply to a 1 <sup>3</sup>/<sub>4</sub>" thick door.


# Delayed egress system components

For all 24 and 25 Series

The delayed egress system provides control for limited egress and high security areas which require accident hazard or fire exit hardware.

## Delayed egress function

When the delayed egress system is armed, the mag lock(s) will remain secure against attempted override pressure and severe impacts. Ingress requires an operational trim, along with access control input (i.e. card reader, key switch, keypad). The system is required to be tied into local fire alarm system.



A complete delayed egress system requires the following components:

- DE5300 is used in delayed exit application and is ideal for controlled areas.
- Key switch operator
- Arm, disarm, reset and bypass the delayed egress system by the mortise cylinder on the dialogue box. (1-1/4" mortise cylinder sold separately.)
- LED status indicator
- Red LED indicates arm. Disarm and alarm status.
- Alarm horn
- Depression of the Falcon 24 or 25 RX device touchpad initiates a local alarm of 100 dB when armed.

## Falcon 25 Series device with RX switch

### PS902 Power supply

- PS902 - The series PS902 power supply is the recommended power supply for use with the delayed egress system. The series PS902 power supply is designed for electric locking or monitoring on single or double door applications. The output power is field selectable for either 24 VDC@1 ampere or 12 VDC@2 ampere. Standard input 120 VAC@0.6 ampere and 240 VAC@3.0 ampere available. The terminal block will accept up to 14 gauge stranded wire.

### Power supply

- **PS900 Series** - A PS900 Series power supply can be safely used with the delayed egress system (see page 39 for more information).

**Magnetic locks** - Schlage electronics M420, M450 or M490 maintains UL listing.

### How to order:

All components above are sold separately. To order, specify each component to complete a delayed egress system for your application.


# Application and wiring

## Popular delayed egress diagram

### Minimum door opening sizes

(Jamb to jamb, or for double door- jamb to center of opening)

| Device | Door size | Door strike | DE5300 for standard devices |
|--------|-----------|-------------|-----------------------------|
| 24-R   | 3'        | 299         | 2' 7 1/2"                   |
|        |           | 264         | 2' 7 3/8"                   |
|        |           | 1439        | 2' 6 3/4"                   |
|        |           | 1606        | 2' 7 1/8"                   |
| 24-R   | 4'        | 299         | 3' 1 1/2"                   |
|        |           | 264         | 3' 1 3/8"                   |
|        |           | 1439        | 3' 1 1/8"                   |
|        |           | 1606        | 3' 1 1/8"                   |
| 24-C   | 3'        | All         | 2' 7 1/8"                   |
| 24-C   | 4'        | All         | 3' 1 1/8"                   |
| 25-R   | 3'        | 299         | 2' 7 3/4"                   |
|        |           | 264         | 2' 7 3/8"                   |
|        |           | 1439        | 2' 6 3/4"                   |
|        |           | 1606        | 2' 7 1/8"                   |
| 25-R   | 4'        | 299         | 3' 1 1/2"                   |
|        |           | 264         | 3' 1 3/8"                   |
|        |           | 1439        | 3' 1 1/8"                   |
|        |           | 1606        | 3' 1 1/8"                   |
| 25-C   | 3'        | All         | 2' 7 3/8"                   |
| 25-C   | 4'        | All         | 3' 1 3/8"                   |
| 25-M   | 3'        | All         | 2' 7 1/2"                   |
| 25-M   | 4'        | All         | 3' 2"                       |



# Electric lock or unlock trim

## Electric lock or unlock trim (FSA/FSE) for 25 Series

The electric lock or unlock (FSA/FSE) feature allows the controlling of trim while still maintaining free egress at all times. The lock or unlock command can be controlled by a security system, fire alarm system, key switch, card reader, push button or touchpad.

**FSA** (Fail safe—unlocks when power is interrupted) can be used in areas requiring doors to be unlocked due to fire, power failure or emergency situations. (Examples: stairwells, hospitals, fire exits, etc.)

**FSE** (Fail secure—locks when power is interrupted) can be used in areas requiring doors to be locked for security reasons and only unlocked when energized by authorized personnel. (examples: banks, inner-office, etc.) With either feature, authorized personnel can gain access utilizing key by overriding or bypassing electric locking function.



### Specifications

- Solenoid rated for continuous duty at 24V DC 0.4 amps.
- UL listed devices.
- Device channel is used as conduit on 25 Series devices.
- Power transfer (EPT-2) hinge 2-wire minimum rated 1/2 Amp.
- See page 35 for more information

### Wire chart

| Length of wire run (ft.) | 24VDC<br>0.4 AMPS |
|--------------------------|-------------------|
| 0-500                    | 18AWG             |
| 501-700                  | 16AWG             |

### How to order

To order FSA/FSE feature, add FSA or FSE prefix to device designation. (Example: FSA 25-R-L)

### Note:

1. FSA/FSE can be used on all devices.
2. The FSA/FSE feature can be used in conjunction with MEL (Motorized electric latch retraction), EA (exit alarm) and security monitoring (DM, LM, RX).

### Minimum power supply- PS902

- The series 902 power supply is the recommended power supply for use with an FSA or FSE trim. The series 902 power supply is also designed for electric locking or monitoring of single or double door applications.
- See page 32 for more information

# Exit alarm

Exit alarm (EA) - for all 24 and 25 Series devices

The Exit alarm (EA) feature provides a battery powered exit alarm to allow for a simple and effective means of monitoring the use of exits while still maintaining means of egress (for code requirements). When the touchbar is depressed the alarm will sound continuously, indicating that the exit has been engaged. The exit alarm can only be reset by way of a standard 1 1/4" mortise cylinder with standard "A" cam (5/16" wide x 3/4" long). The design of the unit will allow the single 9V battery to last for at least six months (on standby mode).



## Minimum door width required for standard devices

| Device  | Door size | Door strike | Min door opening width |
|---------|-----------|-------------|------------------------|
| EA-24-R | 3'        | 299         | 2' 9 1/4"              |
|         |           | 264         | 2' 9 1/8"              |
|         |           | 1439        | 2' 8 3/8"              |
|         |           | 1606        | 2' 8 7/8"              |
| EA-24-R | 4'        | 299         | 3' 3 1/4"              |
|         |           | 264         | 3' 3 1/8"              |
|         |           | 1439        | 3' 3 7/8"              |
|         |           | 1606        | 3' 3 7/8"              |
| EA-24-C | 3'        | All         | 2' 9 1/8"              |
| EA-24-C | 4'        | All         | 3' 3 1/8"              |
| EA-24-V | 3'        | All         | 2' 8 7/8"              |
| EA-24-V | 4'        | All         | 3' 2 7/8"              |
| EA-25-R | 3'        | 299         | 2' 9 1/4"              |
|         |           | 264         | 2' 9 1/8"              |
|         |           | 1439        | 2' 8 3/8"              |
|         |           | 1606        | 2' 8 7/8"              |
| EA-25-R | 4'        | 299         | 3' 3 1/4"              |
|         |           | 264         | 3' 3 1/8"              |
|         |           | 1439        | 3' 3 7/8"              |
|         |           | 1606        | 3' 3 7/8"              |
| EA-25-C | 3'        | All         | 2' 8 7/8"              |
| EA-25-C | 4'        | All         | 3' 2 7/8"              |
| EA-25-M | 3'        | All         | 2' 9 1/4"              |
| EA-25-M | 4'        | All         | 3' 3 1/4"              |
| EA-25-V | 3'        | All         | 2' 8 7/8"              |
| EA-25-V | 4'        | All         | 3' 2 7/8"              |

## Specifications

- Works with rim, mortise, concealed, surface vertical rod
- UL listed
- The EA feature can be used in conjunction with FSA/FSE (Fail safe/Fail secure trim) and security monitoring (DM, LM, RX) features.

## Features and benefits

- 110 dB alarm
- 24 Volt hardwire option
- 9V Battery input
- External inhibit for card reader
- LED indication
  - Armed
  - Disarmed
  - Low battery
  - EAK retrofit kit available for your existing devices

## How to order

To order EA feature add "EA" prefix to device designation. (example: EA-25-R-EO)

To order EAK (exit alarm kit) feature order "EAK" plus device length (3' or 4'), type of device (24 or 25 Series) and the finish of your existing device. (example: EAK-4', 24 Series, US10) (For retrofit application)

## Minimum power supply - PS902

The series PS902 power supply is the recommended power supply for use with the exit alarm (EA) option. The series PS902 power supply is designed for electric locking or monitoring on single or double door applications (see page 32 for more information).

# Device monitoring

Device monitoring for most 24 and all 25 Series devices\*

All of the monitoring features available from Falcon provide total flexibility and will interface with any security system. All monitoring switches are dry contact type and are contained within the device, allowing for tamper-resistant operation. Security monitoring features allow monitoring of devices, latches, authorized egress and locking levers. A key override option is available. All of the security monitoring features can be used in any combination with any other Falcon feature. Consult factory for special applications.

## **\*DM, \*LM, RX Monitoring**

- The DM (device monitor) feature monitors full latch projection. If the latchbolt is retracted by use of device, or someone tampers with the latchbolt, the switch is activated sending a signal to controlling areas. In devices with the deadlock feature, the deadlatch status is monitored.
- The LM (Latch monitor) feature monitors full latchbolt retraction. When the latchbolt is fully retracted a signal is sent indicating door (or device) opened status.
- The RX feature monitors the depression of the touch bar or crossbar. Activation of the switch indicates use of a door or that the door is in the dogged condition. This feature is especially useful when used to activate or shunt magnetic locking systems.
- \*LM/DM not available on F-24-R.

## **How to order**

To order any individual or combination of monitor feature(s) add the respective prefix(s) to device designation. (example: EL-RX-DM-25-V-L-DANE)

## **Key override option (KOR)**

The KOR feature allows authorized personnel to override monitoring features on a door by use of a keyed 1 1/8" mortise cylinder with 5/16" wide x 3/4" long standard cam (mortise cylinder not supplied).

Activating KOR feature allows any feature to be disabled for daytime use or when desired by key holder. This is a maintained contact switch. KOR is especially useful for turning on or off magnetic locking systems and electric dogging control (at the door).

This feature is not available with EA feature, cylinder/standard dogging.

To order KOR feature add KOR prefix to device designation. (example: KOR-DM-24-R-TP)

Note: Use of these features may require a power transfer hinge (supplied by others) or additional wires in the power transfer hinge needed for application when combined with other electrified features.

# Power supply



The PS900 Series is a consolidated line of power supplies and accessories that offer enhanced flexibility and functionality specific to the changing needs of the access control market. The PS900 Series can be used in a variety of applications to convert high voltage AC power into the low voltage DC outputs required by most access control devices. The PS900 Series protects devices downstream by providing Class 2\*, filtered and regulated power. The full line is UL294 certified.

Note: PS906 can provide Class 2 rated outputs when used with 900-8P distribution board.

## Features:

- Constant output rating at both 12 VDC and 24 VDC provides superior performance; includes field selectable jumper
- Polarized connectors for option boards eliminate need for racks and side connectors
- Flat mounting of option boards provides easier access to terminal blocks for connection of electrified devices
- High voltage protective cover
- Battery back-up board auto-selects voltage
- Fire alarm relay can be configured to provide either switched or un-switched outputs from a power supply
- PS914 designed with high in rush current for powering solenoid-driven electrified panic devices
- Universal 120-240 VAC input
- Low voltage DC, regulated and filtered
- Electronic power limiting foldback circuit for AC current overload protection
- Fused primary input
- AC status monitor- isolated SPDT contacts
- AC input and DC output LED status indicators
- Cover mounted AC input indication
- Hinged cover with lock down screws

## Certifications:

- UL 294 certified—the standard for access control
- Class 2 rated\*  
\* Except PS906, output rating exceeds Class 2 power limits

Once power is converted to low voltage DC, the PS900

Series offers a variety of distribution options, including basic fuse protection, simple relay, and advanced logic providing complex sequencing and timing functions.

\* PS906 can provide Class 2 rated outputs when used with 900-8P distribution board.

|  | PS902         | PS904         | PS906         | PS914         |
|--|---------------|---------------|---------------|---------------|
| <b>Number of connectors on power supply for the following:</b> | <b>2 amps</b> | <b>4 amps</b> | <b>6 amps</b> | <b>4 amps</b> |
| Distribution boards  | 1             | 2             | 3             | 2             |
| Battery back-up board  | 1             | 1             | 1             | 1             |

Note: One fire alarm board can be connected directly to the PS902. If a fire alarm board is desired for the PS904, PS906 or PS914 it can be connected to a distribution board.

## Applications:

The PS900 Series of power supplies works with many electrified devices including Falcon exit devices, electromagnetic locks, hardwired locks, electrified mechanical locks, electrified strikes and many other products.

## Accessories:

The PS900 Series features seven option boards for use in a variety of applications. All PS900 Series power supplies option boards are UL 294 certified.

### Option boards:

**900-4R:** 4 relay controlled output board to power multiple devices.

**900-4RL:** 4 relay distribution board with logic is field configurable for time delay function, auto operator, security interlock.

**900-8F:** Provides 8 individually fuse-protected outputs, giving the flexibility to power multiple devices and provide another layer of protection.

**900-FA:** Emergency interface relay integrates with fire alarm and is used to cut power in case of emergency.

**900-BB:** Battery backup.

**900-2RS:** 2 relay MEL or EL panic device control board.

**900-BBK:** Battery backup kit includes two 7A/hr batteries and provides up to four hours of backup power when cycled every 5 minutes at full load.

### Wire selection size/type

| Run length (one way) | MEL device w/EPT, electric hinge, door loop |
|----------------------|---|
| 200'                 | 18 AWG                                      |
| 320'                 | 16 AWG                                      |
| 500'                 | 14 AWG                                      |
| 800'                 | 12 AWG                                      |



# Electrical options summary

## Electrical options matrix - 25 Series

| Option                                    | Electric dogging | Motorized electric latch retraction (MEL) | Delayed egress | Electric lock /unlock trim (FSA/FSE) | Device monitor (DM) | Latch monitor (LM) | Authorized egress (RX) | Key override (KOR) | Exit alarm (EA) |
|---|------------------|---|----------------|--------------------------------------|---------------------|--------------------|------------------------|--------------------|-----------------|
| Motorized electric latch retraction (MEL) | X                | —   | V              | V                                    | V                   | V                  | V                      | X                  | X               |
| Delayed egress                            | V                | V   | —              | V                                    | V                   | V                  | V                      | V                  | V               |
| Electric lock/unlock trim (FSA/FSE)       | V                | V   | V              | —                                    | V                   | V                  | V                      | V                  | V               |
| Device monitor (DM)                       | V                | V   | V              | V                                    | —                   | V                  | V                      | V                  | V               |
| Latch monitor (LM)                        | V                | V   | V              | V                                    | V                   | —                  | V                      | V                  | V               |
| Request to exit (RX)                      | V                | V   | V              | V                                    | V                   | V                  | —                      | V                  | V               |
| Key override (KOR)                        | X                | X   | V              | V                                    | V                   | V                  | V                      | —                  | X               |
| Exit alarm (EA)                           | X                | X   | V              | V                                    | V                   | V                  | V                      | X                  | —               |

## Electrical options matrix - 24 Series

| Option                                    | Electric dogging | Motorized electric latch retraction (MEL) | Delayed egress | Device monitor (DM) | Latch monitor (LM) | Authorized egress (RX) | Key override (KOR) | Exit alarm (EA) |
|---|------------------|---|----------------|---------------------|--------------------|------------------------|--------------------|-----------------|
| Motorized electric latch retraction (MEL) | X                | —   | V              | V                   | V                  | V                      | X                  | X               |
| Delayed egress                            | V                | V   | —              | V                   | V                  | V                      | V                  | V               |
| Device monitor (DM)*                      | V                | V   | V              | —                   | V                  | V                      | V                  | V               |
| Latch monitor (LM)*                       | V                | V   | V              | V                   | —                  | V                      | V                  | V               |
| Request to exit (RX)                      | V                | V   | V              | V                   | V                  | —                      | V                  | V               |
| Key override (KOR)                        | X                | X   | V              | V                   | V                  | V                      | —                  | X               |
| Exit alarm (EA)                           | X                | X   | V              | V                   | V                  | V                      | X                  | —               |

\*Not available on 24-R/F-24-R.

**V** = works with

**X** = doesn't work

# How to order

## 25 Series

|   | MEL                                      | F           | 25           | V                      | L-DANE       | US3  | 3' | LHR | LBR | SNB | WD |
|---|--|-------------|--------------|------------------------|--------------|--|----|-----|-----|-----|----|
| <b>Prefixes</b>   |  |             |              |                        |              |  |    |     |     |     |    |
| <b>CD</b>   | Cylinder dogging                         |             |              |                        |              |  |    |     |     |     |    |
| <b>RX</b>   | Touchbar request to exit                 |             |              |                        |              |  |    |     |     |     |    |
| <b>DM</b>   | Latchbolt and device monitor switch      |             |              |                        |              |  |    |     |     |     |    |
| <b>EA</b>   | Exit alarm                               |             |              |                        |              |  |    |     |     |     |    |
| <b>KOR</b>  | Key bypass switch                        |             |              |                        |              |  |    |     |     |     |    |
| <b>LD</b>   | Less dogging                             |             |              |                        |              |  |    |     |     |     |    |
| <b>LM</b>   | Latchbolt status switch                  |             |              |                        |              |  |    |     |     |     |    |
| <b>MEL</b>  | Motorized electric latch retraction      |             |              |                        |              |  |    |     |     |     |    |
| <b>FSA</b>  | Electric lock or unlock trim-fail safe   |             |              |                        |              |  |    |     |     |     |    |
| <b>FSE</b>  | Electric lock or unlock trim-fail secure |             |              |                        |              |  |    |     |     |     |    |
| <b>Rating</b>   |  |             |              |                        |              |  |    |     |     |     |    |
| <b>F</b>  | Fire exit hardware                       |             |              |                        |              |  |    |     |     |     |    |
| <b>Blank</b>  | Panic exit hardware                      |             |              |                        |              |  |    |     |     |     |    |
| <b>Device series</b>                                    |  |             |              |                        |              |  |    |     |     |     |    |
| <b>25</b>   | Touch bar device, wide stile             |             |              |                        |              |  |    |     |     |     |    |
| <b>Device type</b>                                      |  |             |              |                        |              |  |    |     |     |     |    |
| <b>R</b>  | Rim                                      |             |              | <b>C-WDC</b>           |              | Concealed vertical rod wood door (20 or 90 min)      |    |     |     |     |    |
| <b>V</b>  | Surface vertical rod                     |             |              |                        |              |  |    |     |     |     |    |
| <b>C</b>  | Concealed vertical rod                   |             |              | <b>M</b>               |              | Mortise  |    |     |     |     |    |
| <b>Trim function (see trim pages for all functions)</b> |  |             |              |                        |              |  |    |     |     |     |    |
| <b>EO</b>   | Exit only                                |             |              | <b>K</b>               |              | Knob   |    |     |     |     |    |
| <b>DT</b>   | Dummy trim                               |             |              | <b>L</b>               |              | Lever (Dane standard)                                |    |     |     |     |    |
| <b>NL</b>   | Night latch                              |             |              | <b>C</b>               |              | Cylinder prim plate                                  |    |     |     |     |    |
| <b>NL-OP</b>  | Night latch optional pull                |             |              | <b>511-L</b>           |              | VR trim  |    |     |     |     |    |
| <b>TP</b>   | Thumbpiece                               |             |              |                        |              |  |    |     |     |     |    |
| <b>Finish</b>   |  |             |              |                        |              |  |    |     |     |     |    |
| <b>US3</b>  | <b>US10</b>                              | <b>US11</b> | <b>US15</b>  | <b>US19</b>            | <b>US26</b>  |  |    |     |     |     |    |
| <b>US32</b>   | <b>US28</b>                              | <b>US4</b>  | <b>US26D</b> | <b>US32D</b>           | <b>313AN</b> |  |    |     |     |     |    |
| <b>Door width</b>                                       |  |             |              |                        |              |  |    |     |     |     |    |
| <b>3'</b>   | Standard default                         |             |              | <b>Door thickness</b>  |              |  |    |     |     |     |    |
| <b>4'</b>   |  |             |              | <b>1 3/4" Standard</b> |              |  |    |     |     |     |    |
|   |  |             |              | <b>2 1/4" Optional</b> |              |  |    |     |     |     |    |
| <b>Handing</b>  |  |             |              |                        |              |  |    |     |     |     |    |
| <b>RHR</b>  | Right hand reverse                       |             |              |                        |              |  |    |     |     |     |    |
| <b>LHR</b>  | Left hand reverse                        |             |              |                        |              |  |    |     |     |     |    |
| <b>Less bottom rod</b>                                  |  |             |              |                        |              |  |    |     |     |     |    |
| <b>LBR</b>  | Less bottom rod                          |             |              |                        |              |  |    |     |     |     |    |
| <b>Accessories</b>                                      |  |             |              |                        |              |  |    |     |     |     |    |
| <b>CYL</b>  | Cylinder                                 |             |              | <b>SNB</b>             |              | Sex bolts  |    |     |     |     |    |
| <b>SK</b>   | Shim kit                                 |             |              | <b>AMS</b>             |              | All machine screws (for vertical and concealed only) |    |     |     |     |    |
| <b>Other miscellaneous door information</b>             |  |             |              |                        |              |  |    |     |     |     |    |
| <b>HMD</b>  | Hollow metal door                        |             |              | —                      |              | Door thickness                                       |    |     |     |     |    |
| <b>HMF</b>  | Hollow metal frame                       |             |              | —                      |              | Door undercut  |    |     |     |     |    |
| <b>WD</b>   | Wood door                                |             |              | —                      |              | Door label   |    |     |     |     |    |
| <b>WDF</b>  | Wood frame                               |             |              | —                      |              | Stile width  |    |     |     |     |    |
| <b>ALD</b>  | Aluminum door                            |             |              | —                      |              | Frame stop height                                    |    |     |     |     |    |
| <b>ALF</b>  | Aluminum frame                           |             |              | <b>SGL</b>             |              | Single door  |    |     |     |     |    |
| <b>SCDC</b>   | Steel channel door construction          |             |              | <b>PR</b>              |              | Pair of doors swinging same direction                |    |     |     |     |    |
| —   | Specify other door or frame              |             |              |                        |              |  |    |     |     |     |    |
| —   | Material information                     |             |              |                        |              |  |    |     |     |     |    |
| —   | Door height                              |             |              |                        |              |  |    |     |     |     |    |

# How to order

## Trim

|   |   | 510         | L                     | R           | US26D        | LHR         | SUTRO | FSE | CYL |
|---|---|-------------|-----------------------|-------------|--------------|-------------|-------|-----|-----|
| <b>24 Series</b>  | <b>25 Series</b>  |             |                       |             |              |             |       |     |     |
| 711   | 510   |             |                       |             |              |             |       |     |     |
| 712   | 511   |             |                       |             |              |             |       |     |     |
| 715   | 512   |             |                       |             |              |             |       |     |     |
| 717   | 513   |             |                       |             |              |             |       |     |     |
| 718   | 717   |             |                       |             |              |             |       |     |     |
|   | 718   |             |                       |             |              |             |       |     |     |
| <b>Trim function (see trim pages for all functions)</b> |   |             |                       |             |              |             |       |     |     |
| <b>EO</b>   | Exit only   | <b>K</b>    | Knob                  |             |              |             |       |     |     |
| <b>DT</b>   | Dummy trim  | <b>L</b>    | Lever (Dane standard) |             |              |             |       |     |     |
| <b>NL</b>   | Night latch   | <b>KIL</b>  | Key in lever          |             |              |             |       |     |     |
| <b>C</b>  | Cylinder trim less pull                                   | <b>TL</b>   | Thumb lever           |             |              |             |       |     |     |
| <b>TP</b>   | Thumbpiece  |             |                       |             |              |             |       |     |     |
| <b>Device type</b>                                      |   |             |                       |             |              |             |       |     |     |
| <b>R</b>  | Rim   |             |                       |             |              |             |       |     |     |
| <b>V</b>  | Surface vertical rod                                      |             |                       |             |              |             |       |     |     |
| <b>C</b>  | Concealed vertical rod (includes WDC)                     |             |                       |             |              |             |       |     |     |
| <b>M</b>  | Mortise   |             |                       |             |              |             |       |     |     |
| <b>Finish</b>   |   |             |                       |             |              |             |       |     |     |
| <b>US3</b>  | <b>US4</b>  | <b>US10</b> | <b>US10B</b>          | <b>US11</b> | <b>US15</b>  | <b>US19</b> |       |     |     |
| <b>US26</b>   | <b>US26D</b>  | <b>US32</b> | <b>US32D</b>          | <b>SP28</b> | <b>SP313</b> |             |       |     |     |
| <b>Handing</b>  |   |             |                       |             |              |             |       |     |     |
| <b>RHR</b>  | Right hand reverse  |             |                       |             |              |             |       |     |     |
| <b>LHR</b>  | Left hand reverse   |             |                       |             |              |             |       |     |     |
| <b>Lever style</b>                                      |   |             |                       |             |              |             |       |     |     |
|   | Dane (DAN)  |             |                       |             |              |             |       |     |     |
|   | Sutro (SUT)   |             |                       |             |              |             |       |     |     |
|   | Quantum (QUA)   |             |                       |             |              |             |       |     |     |
|   | Avalon (AVA)  |             |                       |             |              |             |       |     |     |
|   | Boardwalk (BRK)   |             |                       |             |              |             |       |     |     |
|   | Broadway (BRW)  |             |                       |             |              |             |       |     |     |
|   | Danish (DSH)  |             |                       |             |              |             |       |     |     |
|   | Latitude (LAT)  |             |                       |             |              |             |       |     |     |
|   | Longitude (LON)   |             |                       |             |              |             |       |     |     |
| <b>Other miscellaneous door information</b>             |   |             |                       |             |              |             |       |     |     |
| <b>FSA</b>  | Electric Lock or Unlock-Fail Safe (FSA device required)   |             |                       |             |              |             |       |     |     |
| <b>FSE</b>  | Electric Lock or Unlock-Fail Secure (FSE device required) |             |                       |             |              |             |       |     |     |
| <b>CON</b>  | Allegion Connect  |             |                       |             |              |             |       |     |     |
| <b>Accessories</b>                                      |   |             |                       |             |              |             |       |     |     |
| <b>CYL</b>  | Cylinder  |             |                       |             |              |             |       |     |     |
| <b>KD</b>   | Cylinder keyed different                                  |             |                       |             |              |             |       |     |     |
| <b>Door thickness</b>                                   |   |             |                       |             |              |             |       |     |     |
| Specify door thickness other than 1 3/4"                |   |             |                       |             |              |             |       |     |     |

## FALCON®

# Motorized Electric Latch Retraction-MEL

Featuring 24 and 25 Series  
exit devices



## Overview

Motorized electric latch retraction (MEL) provides energy efficient electronic control of an exit device for an affordable around the door solution. The MEL option is Falcon's® solution of choice for multifamily and commercial real estate facilities where cost competitive electromechanical latch retraction is desired. It is available on Falcon 24 and 25 Series exit devices, except 25-M (mortise).

These devices always provide mechanical egress. Motorized electric latch retraction can be used with credential readers to unlatch doors momentarily for authorized users, or it can be incorporated with systems to retract latches for extended periods of time to allow free entry. This is a convenient alternative to mechanical dogging. Doors with automatic operators also often incorporate exit devices with electric latch retraction.

The MEL option is available on panic and fire rated devices. Because fire exit hardware must be self latching, an automatic fire alarm system must be incorporated to drop power to fire rated MEL devices in case of fire.

## Features and benefits

- MEL option available on 24 and 25 Series exit devices, except 25-M (mortise)
- Energy efficient motorized latch retraction enables longer wire runs and the use of a standard Schlage® power supply with option board
- Modular design allows for a simplified installation of the available MEL Conversion kit to existing mechanical Falcon 24 or 25 exit devices
- On-board installation and troubleshooting diagnostics built into the motor assembly
- Self-calibrating motor assembly
- Pushbar is pulled in electronically when dogged
- Vandal resistant – detects and responds to events of attack and tampering
- Available with Allegion Connect (-CON) on full device and kits

## Specifications compliance

- MEL is designed for use on exit devices that are BHMA Certified to ANSI/BHMA A156.3
- Exit devices with MEL are UL and cUL Listed as "Panic Hardware" (UL 305) and as "Fire Exit Hardware" (UL 10C)
- The MEL Conversion Kit is UL Classified under "Accessories for Single-Point Locks and Latches and Fire Exit Hardware" (UL 10C)

## Electronic specifications

| MEL electrical load |  | MEL wire run lengths |            |
|---------------------|--|----------------------|------------|
| Voltage             | 24 VDC                                   | Distance (one way)   | Wire gauge |
| Current             | 1.0 A Inrush (0.5 sec)<br>0.14 A Holding | 200'                 | 18 AWG     |
|                     |  | 320'                 | 16 AWG     |
|                     |  | 500'                 | 14 AWG     |
|                     |  | 800'                 | 12 AWG     |

## Accessories

The MEL has a low inrush current = 1.0 amps, so it can be used with standard Schlage power supplies. When powering multiple components, verify that the amperage requirement of all components combined does not exceed the power supply output rating. See table below for output ratings.

| Schlage PS902 | Schlage PS904 | Schlage PS906 |
|---------------|---------------|---------------|
| up to 2 amps  | up to 4 amps  | up to 6 amps  |


The MEL device is compatible with the following equipment: PS900 Series power supplies - PS902, 904, 906, 914; 900 Series Option Boards - 900-2RS, 900-4R and 900-4RL. The power transfer (EPT, electrified hinge, or door loop) is also sold separately. Please refer to Falcon catalog for more information on EPT-2/EPT-10 power transfers, electrified hinges, and PS900 series power supplies.

## How to order

- To order the MEL feature add "MEL" prefix to device designation (example: MEL-25-R-EO). NOTE: Mechanical dogging is not an option with MEL.
- To order the MEL conversion kit, please specify finish with part number (US3, US4, US10, US26, US26D, US32D, SP28, SP313). MEL conversion kits are only compatible with mechanical Falcon 24 and 25 series exit devices. MEL kits may not be used to convert an EL device.

| Model No. | Description                                   | Part number | Part number with Allegion Connect (-CON) |
|-----------|---|-------------|--|
| 25-MELK-3 | 25 Motorized Electric Latch Retraction Kit 3' | 47266630    | 47270546                                 |
| 25-MELK-4 | 25 Motorized Electric Latch Retraction Kit 4' | 47266631    | 47270547                                 |
| 24-MELK-3 | 24 Motorized Electric Latch Retraction Kit 3' | 47266632    | 47270548                                 |
| 24-MELK-4 | 24 Motorized Electric Latch Retraction Kit 4' | 47266633    | 47270549                                 |

## Popular application



## About Allegion

Allegion (NYSE: ALLE) is a global pioneer in safety and security, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion produces a range of solutions for homes, businesses, schools and other institutions. Allegion is a \$2 billion company, with products sold in almost 130 countries. For more, visit [www.allegion.com](http://www.allegion.com).

KRYPTONITE ■ LCN ■  ■ STEELCRAFT ■ VON DUPRIN



© 2019 Allegion  
012500, Rev. 03/19  
[www.allegion.com/us](http://www.allegion.com/us)