

A
Hinges & Pivots

B
Pulls & Plates

C14
Flush Bolts & Coordinators

D
Latches, Catches & Bolts

E
Stops

F
Exterior Hardware

G
Miscellaneous Hardware

COR7G and COR9G



Meets ANSI/BHMA A156.3, Type 21.
UL Listed for Fire Doors.

Gravity Coordinators

- When active door is open, coordinator prevents active door from closing until inactive door bypasses. Closing of inactive door causes strike plate on top of door to contact cam and lift arm, allowing active door to close. As inactive door continues closing, roller rides over strike plate on to door bracket, holding arm above active door.
- Non-handed.
- Gravity action arm and door bracket are adjustable on the job for ease of installation. Rubber roller provides quiet and efficient operation, and helps protect the astragal and doors from damage.
- Nylon roller on short arm glides smoothly over door bracket and strike, ensuring silent operation.
- Made of forged brass.
- COR7G for use on pairs of doors with astragal on active door up to 4' or with astragal on inactive door up to 3'4" or with astragal on both doors up to 2'10"
- COR9G for use on pairs of doors with astragal on active over 4' or with astragal on inactive door over 3'4" or with astragal on both doors over 2'10"

| Product | Projection |
|---------|------------|
| COR7G | 7" |
| COR9G | 9" |

Finishes

| Ives Finish | US3 | US4 | US10 | US10B | US26 | US26D |
|-------------|-----|-----|------|-------|------|-------|
| BHMA | 605 | 606 | 612 | 613 | 625 | 626 |



Meets ANSI/BHMA A156.3, Type 21.

CBI Carry Bar

- Used when it is possible for the inactive door to be opened before the active door.
- Prevents damage to the doors and other hardware.
- Nylon roller insures quiet and efficient operation.
- Non-handed.
- All-steel construction.
- Standard sex bolts for mounting.

Finishes

| Ives Finish | US3 | US4 | US10 | US10B | US26 | US26D | SPBLK | USP |
|-------------|-----|-----|------|-------|------|-------|-------|-----|
| BHMA | 605 | 606 | 612 | 613 | 625 | 626 | 622 | 600 |