



Meets ANSI/BHMA 156.16, L12131 for brass

### FS441 Floor Stop

- Accommodates door undercut up to 1-1/2".
- Designed to blend well with all types of construction and provide a minimum of hindrance to cleaning efforts.
- Heavy-Duty cast brass or aluminum construction.
- Replaceable Non-marring rubber bumper.

FS441 packed with expansion shield and tampion for masonry type mounting, and wood screws for drywall mounting.

#### Dimensions

Overall Height: 2-1/8"

Overall Length: 2-7/8"

Base Depth: 1-5/8"

#### Finishes *brass*

Ives Number	US3	US4	US5	US10	US10B	US15	US26	US26D
BHMA	605	606	609	612	613	619	625	626



FS444  
Meets ANSI/BHMA 156.16, L12131 for brass

FS448  
Meets ANSI/BHMA 156.16,  
L12121 for brass and L32121 for aluminum

### FS444 Floor Stop

### FS448 Floor Stop

- Ideal for interior or exterior use.
- Cast brass construction.
- Accommodates door undercut up to 2-1/2".
- Replaceable Non-marring rubber tip.

FS444 is packed with expansion shield and lead shield, for masonry type mounting.  
FS448 is packed with wood screws, for drywall mounting.

#### Dimensions

Overall Height: 3"

Base Diameter: 2-1/2"

#### Finishes *brass*

Ives Number	US3	US4	US5*	US10	US10B	US15	US26	US26D
BHMA	605	606	609	612	613	619	625	626

#### Finishes *aluminum*

Ives Number US28\*

BHMA 628

\* not available on FS444

A  
Hinges & Pivots

B  
Pulls & Plates

C  
Flush Bolts & Coordinators

D  
Latches, Catches & Bolts

E6  
Stops

F  
Exterior Hardware

G  
Miscellaneous Hardware