


The 2610 AUTO EQUALIZER™ is LCN's pneumatically powered MULTI-DOOR solution. This low-energy power operator provides easy access for people with disabilities, or the elderly. Designed primarily for manual opening applications that occasionally require automatic opening.

Certifications	Grade 1 - ANSI A117.1, A156.19 UL228, ADA, 100 Hour Salt Spray, Meets BAA - Buy American Act	
Body Construction	 Cast Iron Body Full Complement Bearing 1-1/2" Diameter Piston 11/16" Diameter Double Heat Treated Pinion Journal 	
Fluid	All Weather Fluid	
Handing	Handed	
Size	Sized 3 and 4	
Warranty	2 years	

Fasteners	Wood and machine screws	
Mounting	Concealed, in frame	
Arms	Single lever arm, mounting/finish plate, standard track	
Finishes/Colors/ Powder Coat	 Aluminum (689) Statuary Bronze (690) Light Bronze (691) Black (693) Dark Bronze (695) Brass (696) Custom colors optional 	
	Optional SRI primer - powder coat onlyOptional plated finishes	

Special Templates Customized installation templates or products may be available to solve unusual applications. Contact LCN Product Support for assistance.



AVAILABLENOT AVAILABLE

& Meets ADA requirements (power mode).




^{*} See individual series for maximum manual opening.

2610 Series *Auto Equalizer*

Mounting details

Concealed Mounting



Butt Hinges	Should not exceed 5" (127 mm) in width	
Auxiliary Stop	Recommended	
Head Frame	Minimum 4" (102 mm) x 4" for hollow metal or aluminum tube construction	
Top Rail	 1-3/8" (35 mm) mortise required 5/16" (8 mm) cutout required at top of the door, push side only 	
System Diagram	See "AUTOMATIC OPERATORS" section pages 8-9 for typical system wiring, and pages 28-29 for electrical and pneumatic data for control boxes	
Maximum opening	 Butt hinge template allows 90° power opening and 160° manual opening Please note that many track style door closers are capable of allowing 180° of door swing Track style closers are at their weakest closing force at 180° Consult factory for applications where exterior or large/heavy door must swing 180° Consult factory for all pivot mounted installations 	

Notes:

- · For interior or exterior doors
- · Single acting cylinder in head frame
- · Concealed arm and track in door top rail
- \cdot Consult factory for all pivot mounted installations.
- · Multi-door solution utilizing 10,000,000 cycle heavy duty door closer
- Requires control box with integral compressor or control box using auxiliary air supply. See CONTROL BOX pages 28-29 and actuators and accessories, pages 115-131
- · Guard rails/safety mats not required



Cylinders



2610-3971 Cast Iron Cylinder Assembly

- Handed
- For various applications see
 "Table of Sizes" on 2610 Series page 14
- Standard



2610-3971 DPS Cast Iron Cylinder Assembly

- Handed
- With door position switch which sends signal when door is closed
- Standard



2610-3071 Cast Iron Cylinder Assembly

- Handed
- Mounting plate
- For various applications see "Table of Sizes" on 2610 Series page 14
- Standard



2610-3071 DPS Cast Iron Cylinder Assembly

- Handed
- Mounting plate with door position switch which sends signal when door is closed
- Standard

Arm



2610-3077T Standard Arm

- Handed
- Track roller not included with arm

Track



2610-3038 Standard Track

- Non-handed
- Will not accept hold open clip or bumper assembly
- Standard

Installation Accessories





2610-3034 Track Roller

- Quiet, low friction roller assembly
- Shoulder dimension "X" = 1/16" (2 mm)



2610 Series

Ordering Information

How-to-order 2610 Series

Select cylinder size

- □2613
- □2613 DPS
- □2614
- □2614 DPS

Select hand

- \square RH
- □LH

Specify finish

☐ Standard Powder Coat _____

Aluminum, Dark Bronze, Statuary, Light Bronze, Black, Brass

Closer will be shipped with:

- Standard arm
- Track roller
- Standard track
- Wood & machine screw pack unless options listed below are selected.

Closer options

Finishes

- ☐ Custom Powder Coat (RAL)
- \square Plated Finish, US

Screw pack

☐ Wood & Machine Screw (WMS)

Special template

□ST-____

Table of sizes

Select closer based on width of door

762mm

2614

- Sized 2610 Series cylinders available in size 3 or 4
- Closing power of all 2610 Series closers may be increased 15%

36"

914mm

size 4

Minimum door width

Exterior (and Vestibule) door width


Interior door width




Indicates recommended range of door width for closer size.

NOTE: Minimum door width 30 " (762 mm).

2610 Series "Auto-Equalizer"





Cylinders & Mounting Plate











No.	Description	Part number
1	Activation Decal *	2610-155-2
2	Caution Decal †	2610-155-1
3	Standard Cylinder Assembly (F)(S)(H) [‡]	2613(4)-3071
3	DPS Standard Cylinder Assembly (F)(S)(H) [‡]	2613(4)-3071DPS

No.	Description	Part number
4	Cylinder Only (F)(H)	2613(4)-3971
4	DPS Cylinder Only (F)(H)	2613(4)-3971DPS
5	Spacer	2610-61
6	Mounting/Finish Plate (F)(H)	2610-3002


‡ Includes No. 6.

Please specify finish (F), size (S), and hand (H) where indicated. See the latest edition of the LCN catalog for part descriptions and specifications on many of the items shown above. List prices for items shown above can be located in the current LCN price book.


Blue/White Switch decal.

[†] Black/Yellow Cation decal.

2610 Series "Auto-Equalizer"



Arm & Track



No.	Description	Part number
1	Standard Arm (F)(H)*	2610-3077T
2	Arm Screw (F)	2610-159
3	H Arm Screw	2610-83H
4	Arm & Tube (F) [†]	2610-78
5	Roller Lock Screw	2610-425

No.	Description	Part number
6	Rod (F) [‡]	2610-82
7	Track Roller	2610-3034
8	Standard Track	2610-3038
9	WMS Screw Pack (F)(Not Shown)	2610-WMS

Please specify finish (F) and hand(H) where indicated. See the latest edition of the LCN catalog for part descriptions and specifications on many of the items shown above. List prices for items shown above can be located in the current LCN price book.

^{*} Includes Nos. 2, 3, 4, 5, & 6.

[†] Includes No. 2.

[‡] Includes No. 3 & 5.