


The concealed 6030 Series PACER[®] is a heavy duty, double acting closer designed to fit in a narrow, minimum 1-3/4" header. The single lever arm and roller assembly provides smooth, quiet door control and the choice of finishes and track functions meet virtually all architectural requirements. Installation at left illustrated with center pivot set (not included).

Certifications	Grade 1 - ANSI A156.4, UL 10 C, ADA, 100 Hour Salt Spray, Meets BAA - Buy American Act			
Body Construction	 Cast Iron Body Full Complement Bearing 1-1/8 "Diameter Piston 11/16 "Diameter Double Heat Treated Pinion Journal 			
Fluid	All Weather Fluid			
Handing	Non-Handed			
Size	Sized 1-5			
Warranty	15 years			

Fasteners	Wood Screws and Torx Security Screws (optional)			
Mounting	Concealed (in tube); double acting			
Arms	Standard arm with track			
Finishes/Colors/ Powder Coat	 Aluminum (689) Statuary Bronze (690) Light Bronze (691) Black (693) Dark Bronze (695) Brass (696) Custom colors optional Optional SRI primer - powder coat only Optional plated finishes 			






6030 Series

Mounting details

Concealed Mounting



Auxiliary Stop	Recommended where a door cannot swing 95°	
Center Pivot Set	Must be used but ordered separately	
Door Width	30″ (762 mm) minimum with 1-3/4″ (44 mm) pivot centers	
Top Rail	 1-7/16" (36 mm) mortise required 3/8" (10 mm) cutout required at top of the door, both sides. 	
Door Thickness	1-3/4″ (44 mm) minimum	
Centering Adjustment	Centering is provided by rotating the track roller to center the door in the opening.	
Wood Frame	 Installation simplified by WOOD MOUNTING CLIP SET, 6030-416 Consult product support for special template 	
Maximum opening	 Center pivot template allows 95° Adjustable hold-open points from 85° to 95°, with hold-open track 	

Notes:

For interior or exterior doors

Double acting cylinder in cased frame


· Concealed arm and track in door top rail

· Center pivots only



6030 Series

Accessories



Installation Accessories



6030-416 Wood Mounting Clip Set

- Simplifies mounting closer in wood frame
- Includes latch stile clip, hinge stile clip, and cover
- For use with lves Series center pivots
- Consult factory for special template



6030-169 Track Bumper

- Mounts in track to assist backcheck
- Limits maximum opening
- Consists of bumper, bumper post, and mounting screw

NOTE: Track bumper does not replace auxiliary stop.



6030-3054 Hold-Open Clip

- Mounts in track to provide holdopen function
- Hold-open point controlled by clip location
- Requires 6030-3034H Hold-Open Track Roller



6030-3034 Track Roller

 Quiet, low friction roller assembly includes eccentric with 3/4" (19 mm) adjustment to center 36" (914 mm) door



6030-3034H Hold-Open Track Roller

- Hold-open roller
- Quiet, low friction roller assembly



Ordering information How-to-order 6030 Series closers

Select cylinder size

- □ 6031 □ 6032 □ 6033 □ 6034
- □ 6035

Specify finish

□ Standard Powder Coat _____ Aluminum, Dark Bronze, Statuary, Light Bronze, Black, Brass

Closer options

Track

Hold-open with Bumper (HBUMPER)
 Finishes

 Custom Powder Coat (RAL)_____
 Plated Finish, US______
 SRI primer (use with powder coat finishes only)

Screw pack

□ TORX Machine Screw (TORX)

Table of sizes

- Select closer based on width of door
- 6030 Series cylinders available in size 1, 2, 3, 4, or 5
- Closing power of all 6030 Series closers may be increased 35%
- Specify next higher size closer where strong drafts exist

Exterior (and Vestibule) door width



Interior door width



Indicates recommended range of door width for closer size. Note: Minimum door width 28 ~ (711 mm).

Reduced opening force 6030 Series closers

CAUTION! Any manual door closer, including those certified by BHMA to conform to ANSI Standard A156.4, that is selected, installed and adjusted based on ADA or other reduced opening force requirements may not provide sufficient power to reliably close and latch a door.

Refer to POWER OPERATORS section for information on systems that meet reduced opening force requirements without affecting closing power.

* Maximum opening force.

	DOOR WIDTH	36″	42″	48″
Ŀ	8.5* lbs.	6033	6034	6035
	5.0* lbs.	6031	6032	6032



Installation accessories Wood Clip Set, 6030-416

Closer will be shipped with:

- Standard track with bumper

- Wood and machine screw pack

unless options listed below are selected.


- Standard arm

- Standard cylinder with mounting plate


Special template

□ ST-____

6030 Series "Pacer"



Cylinder & Cover Parts



No.	Description	Part number	No.	Description	Part number
1	Cylinder Assembly (F)(S)	6031(2-5)-3071	4	Arm Screw (F)	6030-159
2	Finish Plate (F)	6030-3002	5	Screw Pack (incl -3034)[Not Shown](F)	6030-WMS
3	Cylinder Only (F)(S)	6031(2-5)-3971	6	Screw Pack (incl -3034)[Not Shown](F)	6030-TORX

Please specify finish (F), size (S), hand (H), & voltage (V) where indicated. See the latest edition of the LCN catalog for part descriptions and specifications on many of the items shown above. List prices for items shown above can be located in the current LCN price book.






6030 Series "Pacer"



Arm Assemblies & Parts



No.	Description	Part number
1	Standard Arm (F)	6030-3077T
2	Track w/Bumper (F)	6030-3038B
2	Track w/Hold Open & Bumper (F)	6030-3038HB
3	Roller Lock Screw (F)	6030-425
4	Arm Screw (F)	6030-83
5	Snubber	6030-157

No.	Description	Part number
6	Track Roller	6030-3034
6	Hold Open Track Roller	6030-3034H
7	Hold-Open Clip	6030-3054
8	Track Bumper	6030-169
9	Wood Clip Set (F)	6030-416

Please specify finish (F), size (S), hand (H), & voltage (V) where indicated. See the latest edition of the LCN catalog for part descriptions and specifications on many of the items shown above. List prices for items shown above can be located in the current LCN price book.

