

## Rockwood K1050 - Metal Kick Plate - Economy Duty .050" Thick



### Specifications:

#### MATERIAL:

.050" Aluminum, Brass, Bronze, Stainless Steel

#### FASTENERS:

#6 x 5/8" Oval Head Sheet Metal Screws

#### FEATURES:

- Push Side Plate Width - 2" less than door width
- Pull Side Plate Width - 1 1/2" less than door width

#### ORDERING:

Specify height x width x finish code. Add any options

#### OPTIONS:

- SA - self-adhesive mounting
- TEK - self-drilling screws
- Beveled 3 or 4 edges, specify B3E or B4E
- Heavy bevel available, specify HVBEV
- CSK - countersunk holes
- Cutouts for locks, louvers, or windows
- TORX - security torx screws

NFPA 80 STANDARDS - 2-4.5 Protection Plates: Factory-installed protection plates shall be installed in accordance with the listing of the door. Field-installed protection plates shall be labeled and installed in accordance with their listing.

Exception: Labeling is not required where the top of the protection plate is not more than 16 in. (406 mm) above the bottom of the door.

NOTE: Finishes US26/625 and US26D/626 are only available up to 24"H.

### Available Finishes:

- US3/605
- US4/606
- US9/611
- US10/612
- US10B/613
- US10BE/613E
- US26/625
- US26D/626
- US28/628
- US32/629
- US32316
- US32D/630
- US32D316
- US32DMS
- Powder Coat

#### WEIGHT:

8" x 34" = 4.0 lbs.

#### ANSI:

J101 - metal armor  
plate

J102 - metal kick plate

J103 - metal stretcher  
& mop plate