

Designer and Manufacturer of Access Ability. Automatic Door Activation Solutions

AA SERIES (All-Active Jamb) Short Form Specifications

AA (1-11/16" x 4-1/2") Automatic Door Opening Jamb Switch by Wikk Industries, Inc.

<u>Features</u>: Smooth rounded corners, high quality images and text, tamper resistant by reason of no visible mounting screws.

Size: 1-11/16" x 4-1/2" (43 mm x114 mm) rectangular cover plate

<u>Logo</u>: Debossed or Engraved with infill colors as shown in literature, or custom Engraved and infilled with your choice of colors-Blue, Black, White, Red, Green and Chocolate Brown.

Material: Type 304 Stainless Steel in brushed finish US32D (630)

Optional Materials/Finishes: US32 (629), US3 (605), US4 (606), and US10B (613)

Switch Mechanism: UL® & CSA tested momentary SPDT snap action switch rated at 15 Amp 125/250 VAC

Mounting Plate: 1-11/16" x 4-1/2" Aluminum, 1/8" thick

Mounting:

Flush mount: mullion or jamb cutout per supplied template

Surface mount: Wikk's JSB 1-3/4 Deep (Jamb Surface Box in Black ABS material)

Switch projection from mounting surface: approximately 3/8" (9.5 mm)

<u>WR (Weather Resistant) option</u>: Rubber boot/panel nut component attached to switch mechanism onto the mounting plate to effectively block dirt and moisture from damaging snap action switch.

Specified in:

MasterFormat® 1995: Section 08 710 Door Hardware

MasterFormat® 2004: Section 08 7120 Automatic Door Controls

From 4SPECS website: Section 08 7120 Door Controllers and Operators CSI 3- Part Format Guide Specifications are available for download on the

Wikk's Website: http://www.wikk.com

Exclusive
Manufacturer of
the
INGRESS'R®



36" inches of enlightened access for automatic doors

Phone Toll Free: 877.421.9490 Phone: 414.421.9490 www. wikk.com Fax Toll Free: 877.421.3158 Fax: 414.421.3158 sales@wikk.com

P.O. Box 167 6169A Industrial Court Greendale, WI 53129-0167