

## **Bollard Post- Square (BPS Series) by Wikk Industries, Inc.**

There are entrances where mounting a wall switch and access controls directly to the wall adjacent to the door is impractical in terms of accessibility guidelines. In other cases a high degree of visibility of these devices is desirable. Utilizing a bollard is a practical solution.

### **Features:**

- 6" square with 1/8" wall
- Black HDPE mortised removable cap with a transmitter mounting strap
- Standard single gang prep located at 36" From Finished Floor (FFF)
- Complete mounting instructions

### **Mounting Options:**

- Surface mount-42" From Finished Floor (FFF) with square U-shaped aluminum bracket with access hole for wiring conduit, (4) 1/2"x 2-3/4" length masonry anchors, (4) 1/4-20 stainless steel flat head machine screws
- In-Ground mount- 54" with 12" recess In-Ground

### **Material:**

- Anodized Aluminum 6063-T5- Clear (628), Dark Bronze (710), Black (711), Light Bronze and Mill Aluminum for painting or powder coating
- 304 Stainless Steel Tube, Satin -US32D(630)
- 304 Stainless Steel Tube, Mirror-US32 (629)
- Clad Aluminum, Satin Brass-US4 (606) uncoated
- Clad Aluminum, Mirror Brass-US3 (605) uncoated

### **Options:**

- Welded Stainless Steel Cap
- Removable Stainless Steel and Brass Caps
- Welded Angle Top
- Removable Angle Top
- Custom heights
- Custom preps
- Multiple preps for additional devices

Exclusive  
Manufacturer of  
the  
**INGRESS'R®**



36" inches of  
enlightened access  
for  
automatic doors