

## **PRODUCT FEATURES**

- 12 key 3x4 keypad with engraved and paint filled numbers
- Stainless steel plate
- · Red, green and yellow LEDs for status and programming feedback
- Audible keystroke echo
- Controller mounted in plastic enclosure
- 59 users
- User code and/or hard code disable feature
- 5A DPDT relay output
- · Request to exit (REX) input
- True 10 digit operation (keys are not paired), 3 LEDs and a beeper
- 16 ft. [4.8m], 12 conductor, 22 gauge keypad cable
- MagnaCare<sup>®</sup> lifetime replacement, no fault warranty

## **PRODUCT OPTIONS**

- Weather-resistant cover (WCC)
- · Weather-resistant back box (WBB)
- Keypad available as system or separately

8" [203mm]

## **SPECIFICATIONS**

**Dimensions:** Keypad: 2-3/4"W x 4-1/2"H x 5/32"D Enclosure: 6"W x 8"H x 3"D

**Electrical:** 12 VAC/VDC: 7 mA at rest; 160 mA active

24 VAC/VDC: 20 mA at rest; 190 mA active

### **Operating Temperature: CPU:** +32 to +158F [0 to +70C]

Kevpad: +32 to +110F [0 to +43C] Indoor use

**Shipping Weight:** 4.2 lbs [1.91kg] **Finishes:** 


US32D/630 - Satin Stainless Steel

# **DK-16 Digital Keypad System**

## Secure, Easy-to-Program Single Door **Control System**

The DK-16 digital keypad system provides medium/high security control of electric locks in a one- or two-door application where both doors have the same control needs. The tamper-resistant 3x4 keypad provides true 10-key operation for use and programming. Encased in a separate enclosure for secure installation in a protected area, the controller offers REX input and relay output for lock control, alarm shunt or other interfaces.

#### >> MODELS PART # | Description **DK-16** Keypad and Controller - Indoor, Single Gang DK-16P Keypad only - Indoor, Single Gang WBB Weather Back Box WCC Weather Cover - Clear







6" [152mm]

NUMBER SA ABLOY

3" [76mm]

