DURABLE



PRODUCT FEATURES

- Ultra-secure collapsing blind nuts mount to the door frame for strength and reliability
- Fully sealed for weatherproof operations
- 10 ft. [3.05m] of jacketed, stranded conductor cable
- Automatic dual-voltage no field adjustment required
- Instant release circuit no residual magnetism
- Noise suppression with included MOV
- Efficient, low power usage
- Rust resistant all ferrous metal surfaces plated for durability
- MagnaCare[®] lifetime replacement, no fault warranty

PRODUCT OPTIONS

- (B) BondSTAT[™] magnetic bond sensor Patented (MBS)
- (D) Integrated door position
 switch (DPS)
- (F) Face drilled
- Split Strike M32SS (see page 40)

SPECIFICATIONS

- UL 10C Listed
- CAN4-S104, CAN/ULC-S533 Listed
- ANSI/UL 294 Listed
- CSA-C22.2 No.205 Listed
- ANSI/BHMA A156.23, Grade 1; E08501-500
- CSFM- California State Fire Marshal Approved
- MEA City of New York Approved
- CE:EN 50081-1(92), EN 61000-6-2(99) Approved
- Environmental Product Declaration

Patent: 8,094,017 Holding Force:

600 lbs [272kg]

Dimensions: Magnalock: 8"L x 1-5/8"D x 1-7/8"H Strike: 6-1/4"L x 1/2"D x 1-5/8"H

Electrical: 300 mA at 12 VDC 150 mA at 24 VDC

Operating Temperature:

-40 to +140F [-40 to +60C] Indoor or Outdoor use

Shipping Weight:

6 lbs [2.72kg]

Finishes: US32D/630 - Satin Stainless Steel

2-1/4"




M32 SERIES 600 lbs Holding Force

The Ultimate in Magnalock® Reliability for Indoor/Outdoor Traffic Control

The M32 electromagnetic lock is ideal for traffic control in high-use areas within secured or monitored perimeters. With unsurpassed durability, the M32 will last long after most buildings wear out. Applications include storage areas, rooms, and hallways where reliability, high durability and low-maintenance are required.

» MODE	LS	PART # Description
M32	M32 Magnalock- 12/24 VDC	
M32B	M32 Magnalock- 12/24 VDC, MBS	
M32BD	M32 Magnalock- 12/24 VDC, MBS, DPS	
M32D	M32 Magnalock- 12/24 VDC, DPS	
M32F	M32 Magnalock- 12/24	/DC, Face Drilled
M32FB	M32 Magnalock- 12/24	/DC, Face Drilled, MBS
M32FBD	M32 Magnalock- 12/24	/DC, Face Drilled, MBS, DPS
M32FD	M32 Magnalock- 12/24	/DC, Face Drilled, DPS

For dress covers and flexible mounting brackets, see page 26





ACCESS CONTRO

GRADE 1

DUAL VOLTAGE

FIRE RATED

JECURITRON[®]

ASSA ABLOY

23